



Lampade nelle versioni sospensione, tavolo, soffitto/parete con montatura in metallo rifinita con vernice poliaccrilica in bianco e diffusore in vetro opale satinato soffiato. Emissione di luce diffusa con possibilità di scelta di varie fonti luminose (LED, E27). Vetro fissato da 2 viti laterali con perfetta e omogenea distribuzione della luce al suo interno, senza presenza di zone in ombra. Nella versione a sospensione tiges telescopica. Ideale per ambienti residenziali/commerciali o strutture hospitality.

Suspension, table, ceiling/wall lamps, metal frame in white polyacrylic paint and diffuser in opal blown glass. Diffused light emission provided by a choice of different light sources (LED, E27). Glass fixed by 2 side screws, perfect and homogeneous distribution of the light without any shadow. Telescopic rods in the suspension version. Ideal for residential/commercial environment and for hospitality facilities.

PAGE CATALOGUE 152	CODICE CODE	FONTI LUMINOSE LIGHT SOURCES	Kgn
	<b>L07001.011.0101</b>	Potenza assorbita apparecchio / Luminaire power consumption 9,5W Flusso luminoso apparecchio / Luminaire luminous flux 667 lm 3000K Ra 80 220-240V	1,45
	<b>L07001.014.0101</b>	Potenza assorbita apparecchio / Luminaire power consumption 13W Flusso luminoso apparecchio / Luminaire luminous flux 954 lm 3000K Ra 80 220-240V	1,95
	<b>A07001.011.0101</b>	Potenza assorbita apparecchio / Luminaire power consumption 9,5W Flusso luminoso apparecchio / Luminaire luminous flux 667 lm 3000K Ra 80 220-240V	0,85
	<b>A07001.011.0000</b>	LED retrofit bulb E14 Lmax. 75mm - Ø max. 45mm max 60W E14	0,90
	<b>A07001.014.0101</b>	Potenza assorbita apparecchio / Luminaire power consumption 13W Flusso luminoso apparecchio / Luminaire luminous flux 954 lm 3000K Ra 80 220-240V	1,45
	<b>A07001.014.0000</b>	LED retrofit bulb E27 Lmax. 100mm - Ø max. 55mm max 70W E27 max 23W Micro Twist E27	1,50

	CODICE CODE	FONTI LUMINOSE LIGHT SOURCES	Kgn
	<b>C07001.011.0101</b>	Potenza assorbita apparecchio / Luminaire power consumption 9,5W Flusso luminoso apparecchio / Luminaire luminous flux 667 lm 3000K Ra 80 220-240V	0,85
	<b>C07001.014.0101</b>	Potenza assorbita apparecchio / Luminaire power consumption 13W Flusso luminoso apparecchio / Luminaire luminous flux 954 lm 3000K Ra 80 220-240V	1,45

Fotometrie e Classi Energetiche disponibili [www.panzeri.it](http://www.panzeri.it) / Photometric data and Energy Label available at [www.panzeri.it](http://www.panzeri.it)

CODICI COLORI DISPONIBILI / COLOUR CODES AVAILABLE

**01** Bianco  
White