



Top: Osprey Waters
 Left: Close up of UV Textured Black
 Above: Wall application


Nova

WALL LIGHT

For a subtle, angular statement choose a rectangular-shaped exterior wall light. This luminaire delivers two-directional warm white light and is rated IP65 for resistance against dust and water infiltration.

- Suitable for indoor and outdoor applications
- Rounded version of the Astro Wall Light
- Available in a UV textured black, white or anodised aluminium finish

Measurements (mm)




Absolute Luminous Flux

7W (500mA)
395lm

Beam

110° (F)

Photometrics



$\alpha = 110^\circ$



Finishes

- UV Textured Black
- UV Textured White
- Anodised Aluminium

General Specifications

Material | Powder Coated Aluminium
 IP | 65
 Warranty | 3 Years

LED

Colour Temp | 3000K
 CRI | 80+
 Efficacy | Up to 46lm/w
 Colour Deviation | SDCM \leq 3
 Lifetime | >50,000h L70


Driver

Power Factor | >0.90
 240V Built-in PC Dimmable Driver
 DALI Driver must be remote.
 Dimming | LED Phase-Cut Dim (PC)
 DALI Dim Optional



Driver (DALI drivers can be configured via Product Toolbox)	Phase Cut Dimmable Driver included	
F	-	-
Beam	Flood	Flood
E	F	F
CCT	30	3000K
D	30	3000K
Finish	Textured Black TB Textured White TW Anodised Aluminium AA	
Power	0007	7W
Product Family	NOVA	Nova Wall Light
A	NOVA	NOVA0007.TB30.F
F	-	Driver
E	F	F
D	30	30
C	TB	TB
B	0007	0007
A	NOVA	NOVA0007.TB30.F

Example: **NOVA0007.TB30.F**
 Refer to data sheet for available configurations.
 Visit Product Toolbox at unios.com/nova to configure compatible Osram/Tridonic DALI drivers.



WALL SURFACE