

# POP

Ceiling

TYPE:

PROJECT NAME:

MODEL #

FINISH

LED COLOR

OPTIC

DRIVER

VOLTAGE



# POP

Marco Pagnoncelli - 2011



Lampada a soffitto dalla forma rettangolare a luce diretta caratterizzata dalla luce a LED 120V e dal profilo disegnato a U, che conferiscono design esclusivo e raffinato sia dal punto di vista estetico che cromatico. Lampada che non necessita di alimentatore.

Disponibile nella temperatura colore LED 3000 °K e 2700 °K.

Classe energetica A++, A+, A

Modello depositato



Ceiling lamp with a rectangular shape and 120V LEDs. The U profile characterizes the exclusive and polished design both aesthetically and chromatically. This lamp doesn't need power supply.

Available with 3000 °K or 2700 °K LED colour temperature.

**TRIAC Dimming - Works with most of the existing TRIAC dimmers.**

Energy class A++, A+, A


Registered design

## FINISH

RS = COPPER SILVER  
 OS = GOLD SILVER  
 BI = WHITE  
 AL = POLISHED ALUMINIUM  
 NE = BLACK  
 MK = MOCHA  
 G = GREY  
 FO = GOLD LEAF  
 OR = BRUSHED GOLD  
 FA = SILVER LEAF



C:



| Art.  | W    | V   | Lumen | °K Led | A cm      | B cm      | C cm    |
|-------|------|-----|-------|--------|-----------|-----------|---------|
| POP5  | 22,5 | 120 | 1750  | 3000   | 45(17.7") | 25(9.8")  | 3(1.2") |
| POP8  | 36   | 120 | 2800  | 3000   | 60(23.6") | 35(13.8") | 3(1.2") |
| POP11 | 50   | 120 | 3850  | 3000   | 90(35.4") | 45(17.7") | 3(1.2") |

INPUT VOLTAGE 120V