



Richie Rail 26 is a unique illuminated handrail system with a diameter of 48.3mm. Hollow wall brackets conceal the power supply to the LED strip, and the low voltage input makes the handrail safe to touch. The innovative sliding wall brackets allow minimal power feeds to the LED strip for simple installation. Richie Rail 26 is suitable for use on residential and commercial stairs and thoroughfares including accessible routes and exterior urban spaces. Richie Rail 26 can be supplied as a "plug-and-play" modular system, or as a seamless, fully welded system.

MOUNTING OPTIONS	DIFFUSER OPTIONS	SUPER SERIES LED STRIP OPTIONS		
Wall mounted	Opal	Lumens per metre	Watts per metre	Colour temp.
	Clear	270lm	2.6W	2700K
		280lm		3000K
		300lm		4000K
		530lm	5W	2700K
		500lm		3000K
		650lm		4000K
		1250lm	11W	2700K
		1270lm		3000K
		1400lm		4000K

- LED strip options vary depending on region – please consult your local distributor for more information. Other LED strip options are available on request, including IP65 and RGBW colour change.  
 - All lumen values refer to the bare LED strip. Losses through diffuser/profile are not represented. Consult photometric data.  
 - 7 year manufacturer's warranty on Super Series LED strip.

## ACCESSORIES



## ADDITIONAL INFORMATION

Applications Commercial stairs, public stairs, accessible routes, exterior urban spaces.  
 Installation Interior or exterior (with IP65 rated LED strip).  
 Materials 316 stainless steel rail and components, extruded aluminium, polycarbonate diffuser.  
 Finish Satin 316 stainless steel.  
 Light source LED ribbon strip.  
 Power supply 24V DC - remote driver options ranging from 6W up to 320W.  
 Dimmable Various options available, please enquire.

